

Technical Sheet

GENERAL PROPERTIES

Form	Liquid
Aspect	Brown viscous liquid
Specific gravity	Liquid – 1300kg/m ³
pH (10% solution)	3,3 ± 1
Solids % m/m	50 ± 1

RISKS

PRECAUTIONS

Fire – not flammable	---
Explosion – not explosive	---
Skin – not irritating	Safety gloves are recommended
Ingestion – not dangerous	Do not ingest
Eyes – not irritating	Safety goggles are recommended

DISPOSAL

Under fresh and dry storage conditions, the product is stable for many years.

PACKAGING

Liquid: 208-liter drum, 1050-liter tote

APPLICATION RATES

Mix-in	Liquid 4 - 5 % on aggregate weight
Spray-on	Liquid 1,5 - 2 lt /m ²

DILUTION RATES

Mix-in application: the product shall be diluted with water. Get the optimum moisture content in order to have a good compaction.

Spray-on application: the product shall be diluted depending on the permeability of the aggregates to be treated and on the weather conditions.

Distributed by:

FULL SERVICE SRL
 Via E. Ferrari, 6
 35046 Saletto (Padova)
 ITALY
 Tel. 0039.0429.841181 Fax 0039.0429.841182
 info@fullservice-it.com
 www.fullservice-it.com